

GUILLEMIN Binnendraad
Aluminium

Guilleminkoppeling zonder grendelring x binnendraad.



Artikel nr.	Materiaal	Draadaansl.	Max. werkdruk bij 20°C	Nokafstand	Norm
4643103	Aluminium	3/4" bi.dr.	16 bar	32 mm	NF E 29572
4643104	Aluminium	1" bi.dr.	16 bar	38 mm	NF E 29572
4643105	Aluminium	1 1/4" bi.dr.	16 bar	43 mm	NF E 29572
4643106	Aluminium	1 1/2" bi.dr.	16 bar	56 mm	NF E 29572
4643107	Aluminium	2" bi.dr.	16 bar	70 mm	NF E 29572
4643108	Aluminium	2 1/2" bi.dr.	16 bar	85 mm	NF E 29572
4643101	Aluminium	3" bi.dr.	16 bar	103 mm	NF E 29572
4643102	Aluminium	4" bi.dr.	16 bar	125 mm	NF E 29572

GUILLEMIN Binnendraad

Aluminium

Guilleminkoppeling met grendelring x binnendraad.



Artikel nr.	Materiaal	Draadaansl.	Max. werkdruk bij 20°C	Mat. afdichting	Nokafstand	Norm
4643003	Aluminium	3/4" bi.dr.	16 bar	NBR	32 mm	NF E 29572
4643004	Aluminium	1" bi.dr.	16 bar	NBR	38 mm	NF E 29572
4643005	Aluminium	1 1/4" bi.dr.	16 bar	NBR	43 mm	NF E 29572
4643006	Aluminium	1 1/2" bi.dr.	16 bar	NBR	56 mm	NF E 29572
4643007	Aluminium	2" bi.dr.	16 bar	NBR	70 mm	NF E 29572
4643008	Aluminium	2 1/2" bi.dr.	16 bar	NBR	85 mm	NF E 29572
4643001	Aluminium	3" bi.dr.	16 bar	NBR	103 mm	NF E 29572
4643002	Aluminium	4" bi.dr.	16 bar	NBR	125 mm	NF E 29572
4643010	Aluminium	6" bi.dr.	16 bar	NBR	160 mm	NF E 29572

**GUILLEMIN Buitendraad
Aluminium**

Guilleminkoppeling zonder grendelring x buitendraad.



Artikel nr.	Materiaal	Draadaansl.	Max. werkdruk bij 20°C	Nokafstand	Norm
4645903	Aluminium	3/4" bu.dr.	16 bar	32 mm	NF E 29572
4645904	Aluminium	1" bu.dr.	16 bar	38 mm	NF E 29572
4645905	Aluminium	1 1/2" bu.dr.	16 bar	43 mm	NF E 29572
4645906	Aluminium	1 1/4" bu.dr.	16 bar	56 mm	NF E 29572
4645902	Aluminium	2" bu.dr.	16 bar	70 mm	NF E 29572
4645907	Aluminium	2 1/2" bu.dr.	16 bar	85 mm	NF E 29572
4645908	Aluminium	3" bu.dr.	16 bar	103 mm	NF E 29572
4645901	Aluminium	4" bu.dr.	16 bar	125 mm	NF E 29572

**GUILLEMIN Buitendraad
Aluminium**

Guilleminkoppeling met grendelring x buitendraad.



Artikel nr.	Materiaal	Draadaansl.	Max. werkdruk bij 20°C	Mat. afdichting	Nokafstand	Norm
4646007	Aluminium	3/4" bu.dr.	16 bar	NBR	32 mm	NF E 29572
4646008	Aluminium	1" bu.dr.	16 bar	NBR	38 mm	NF E 29572
4646009	Aluminium	1 1/2" bu.dr.	16 bar	NBR	43 mm	NF E 29572
4646005	Aluminium	1 1/4" bu.dr.	16 bar	NBR	56 mm	NF E 29572
4646003	Aluminium	2" bu.dr.	16 bar	NBR	70 mm	NF E 29572
4646002	Aluminium	2 1/2" bu.dr.	16 bar	NBR	85 mm	NF E 29572
4646001	Aluminium	3" bu.dr.	16 bar	NBR	103 mm	NF E 29572
4646006	Aluminium	4" bu.dr.	16 bar	NBR	125 mm	NF E 29572
4646010	Aluminium	6" bu.dr.	16 bar	NBR	160 mm	NF E 29572

GUILLEMIN Blindkap
Aluminium

Guilleminkoppeling met grendelring blindkap.



Artikel nr.	Materiaal	Max. werkdruk bij 20°C	Nokafstand	Norm
4643405	Aluminium	16 bar	32 mm	NF E 29572
4643406	Aluminium	16 bar	38 mm	NF E 29572
4643407	Aluminium	16 bar	43 mm	NF E 29572
4643408	Aluminium	16 bar	56 mm	NF E 29572
4643404	Aluminium	16 bar	70 mm	NF E 29572
4643403	Aluminium	16 bar	85 mm	NF E 29572
4643401	Aluminium	16 bar	103 mm	NF E 29572
4643402	Aluminium	16 bar	125 mm	NF E 29572
4643412	Aluminium	16 bar	160 mm	NF E 29572

GUILLEMIN Slangtule **Aluminium**

Guilleminkoppeling met grendelring x *geribde* slangtule met kraag.



Artikel nr.	Materiaal	Tuleaansluiting	Max. werkdruk bij 20°C	Mat. afdichting	Nokafstand	Norm
4643332	Aluminium	40 mm	16 bar	NBR	56 mm	NF E 29572
4643303	Aluminium	50 mm	16 bar	NBR	70 mm	NF E 29572
4643304	Aluminium	65 mm	16 bar	NBR	85 mm	NF E 29572
4643302	Aluminium	75 mm	16 bar	NBR	103 mm	NF E 29572
4643301	Aluminium	100 mm	16 bar	NBR	125 mm	NF E 29572
4643333	Aluminium	150 mm	16 bar	NBR	160 mm	NF E 29572